SAFETY JOGGER INDUSTRIAL



ALLFLEX 4131A

Precision Gloves

ALLFLEX gloves offer agility and sensitivity for delicate assembly. Nylon spandex liner and nitrile coating ensure comfort and precision in dry conditions.

Liner	15 Gauge Polyamide/Elastane/Latex
Coating	Foam Nitrile
Category	SIF-Silicone Free
Size range	EU 6-12
Sample weight	0.020 kg
Norms	ANSI/ISEA 105:2016 : A1 2 4 EN ISO 21420:2020 EN 388:2016 : 4 1 3 1 A

CE | ANSI /ISEA | 15G | DMF FREE PU | LATEX FREE | SILICONE FREE

EN ISO 21420



EN 388:2016



Industries:

Assembly, Automotive, Chemical, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry, Tactical



174

Performance level

EN388:2016	0	1	2	3	4	5
a. Abrasion resistance (cycles)	< 100	100	500	2000	8000	-
b. Cut resistance (Coup test)	< 1.2	1.2	2.5	5.0	10.0	20.0
c. Tear resistance (newton)	< 10	10	25	50	75	-
d. Puncture resistance (newton)	< 20	20	60	100	150	-

EN ISO 13997 (TDM-100 test)	A	B	C	D	E	F
e. Straight blade cut resistance (TDM 100 test)	2	5	10	15	22	30

a. Abrasion resistance: based on the number of cycles required to rub through the sample glove.
b. Cut resistance: based on the number of cycles required to cut through the sample at a constant speed with a rotating blade.
c. Tear resistance: based on the amount of force required to tear the sample.
d. Puncture resistance: based on the amount of force required to pierce the sample with a standard sized point.
e. Cut resistance according TDM100 test based on the number of cycles required to cut through the sample at a constant speed with a sliding blade.

High abrasion resistance
These gloves are built to withstand heavy use without wearing out quickly. They meet the highest level of abrasion resistance according to the EN 388 standard.

High dexterity
These gloves are made from the thinnest knit material available, ensuring the highest level of dexterity, comfort and protection.

SAFETY JOGGER WORKS

HEAD-TO-TOE PROTECTION

ENGINEERED IN EUROPE

www.safetyjogger.com