SH 802 R

ORYX™ Industrial Safety Helmet – Ratchet Lock System

Made in China • CE EN 397:2012+A1:2012 • ANSI/ISEA Z89.1-2014 • 32 pcs per carton

PRODUCT VIEWS



Side View (Worn) – Orange



Three-Quarter View – Milky White

AVAILABLE COLORS Milky White | Yellow | Green | Red | Blue | Orange

PRODUCT HIGHLIGHTS

High Quality, Stylish & Ergonomic
Maximum protection in hazardous working conditions

Adjustable PE Suspension
Ratchet locking system to give a perfect fit

Anti-Bacterial Sweatband
Harness anti-sweat band

Earmuffs
Earmuff provision

Chin Strap
V-type chin strap

KEY DATA

CODE	SH 802 R
DESCRIPTION	ORYX™ Industrial Safety Helmet – Ratchet Lock System
STANDARD COMPLIANCE	CE EN 397:2012+A1:2012 | ANSI/ISEA Z89.1-2014
ORIGIN	China
PACKAGING	32 pcs per carton
MASS	350 g
ADJUSTABLE SIZE	53–63 cm

AVAILABLE AT Armexia

armexia.com

PRODUCT DESCRIPTION

The helmet is designed to provide head protection against falling objects and consequential brain injury and skull fracture. This safety helmet must be correctly installed to ensure proper fit and protection.

KEY FEATURES

- PP (polypropylene) shell
- V-type top reinforcement
- 4-point suspension
- Ratchet adjustment
- Chin strap included
- Harness anti-sweat band

SPECIFICATIONS

Test	Result
Shock absorption	≤ 5 kN
Penetration resistance	PASS
Flame resistance	≤ 5 s
Temperature resistance	-10 °C to +50 °C
Mass	350 g
Adjustable size	53–63 cm

FITTING AND ADJUSTMENT

For adequate protection, this helmet must be adjusted to fit the user's head. Unauthorized helmet alterations are prohibited.

INSTALLING THE SUSPENSION

1. Turn the safety helmet shell upside down. Place the suspension inside the safety helmet shell with the brow pad toward the front bill.
2. Insert the suspension tab into the respective slot firmly until it locks into place. Repeat for each suspension tab.

ADJUSTING THE SUSPENSION SIZE

- Turn the ratchet knob counterclockwise until the headband opens to its largest size.
- Place the helmet on your head and turn the ratchet knob clockwise until the headband is comfortable.
- Do not overtighten.

STORAGE AND USE LIFE

- When not in use or during transportation, this helmet should be stored in a container with paper or foam cushioning to avoid damage.
- Store in a ventilated place without direct sunlight and away from contact with any solvent.
- The suspension should be replaced after no more than **12 months** of use.
- The validity of the safety helmet is **30 months** when the helmet is stored in the correct conditions and is properly maintained.
- Always replace the helmet after it has withstood an impact or penetration.

PACKING AND SHIPPING

Item	Detail
Carton packaging	32 pcs per carton
Stacking height	Shall not exceed 5 cartons
Handling	Handle with care; avoid heavy pressure, strong impact and water spray

MANUFACTURER DETAILS

Brand: ORYX™ – The Protector | **Company:** Eyevex – Our Vision. Your Safety
Website: www.eyevexafety.com | **Made in:** China

AVAILABLE AT Armexia
armexia.com