



jalas® GRAN PREMIO 1948S METATARSAL

ASTM F2413-18 M/I/C/Mt/PR ASTM F3445-21 SR EN ISO 20345:2011 S3, SRC, HRO, M, CI, HI

Learn more

METATARSAL IMPACT PROTECTION BOOT

A durable boot for heavy industrial work, with extreme heat resistance and great comfort. Provides the highest protection for welding and heat. Integrated impact protection of the metatarsal part of the foot. Nitrile outsole for excellent grip and excellent shock absorption with PORON® XRD in the insole. Nail protection in plasma-treated composite and toecap in aluminium for low weight. Full grain leather for good fit. A boot with the highest level of protection and comfort.

CHARACTERISTICS

- High level of protection
- Excellent grip
- Good fit
- Extra comfortable
- Excellent shock absorption

FUNCTIONS

- ProNose toe reinforcement
- Wide fit
- KEVLAR® thread in the seams which resists 427° C short-term heat exposure (max operating limit) and 204° C longer-term heat exposure (constant operating limit)
- Heat-resistant upper
- Heat-resistant outsole
- Oil-resistant outsole
- Anti-static properties
- Padded boot shaft
- Adjustable ankle strap
- Pull loops
- Water repellent
- Flame retardant
- Specially designed details
- Double shock absorption zones

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.

PREVENTS RISK OF

Toe injuries, Nail penetration, Metatarsal injuries

PRIMARY ENVIRONMENTS OF USE

Outdoors, Indoors, All-year use, Warm surfaces, Environments with risk for outsole penetration, Oily and greasy environments, Dirty environments, Harsh environments

PRIMARY AREAS OF USE

Hot work, Metalwork, Sheet-metal work, Welding

PRIMARY INDUSTRIES OF USE

Basic metals manufacturing

SPECIFICATION

TYPE Safety footwear, Boots/Ankle boots
CATEGORY Cat. II
NAIL PROTECTION MATERIAL Plasma-treated composite (PTC) textile
FITTING Wide
COLLECTION Gran Premio
UPPER MATERIAL Full-grain leather
PRONOSE MATERIAL PU
TOECAP MATERIAL Aluminium
LINING MATERIAL Polyester, polyamide
INSOLE JALAS 8217 FX2 Climate
INNERSOLE MATERIAL Textile, Soft EVA, Polyester-based conductive thread, Merino wool, Double shock absorption zones in PORON® XRD®
MIDSOLE MATERIAL PU midsole
OUTSOLE MATERIAL Nitrile rubber outsole
FASTENING Hook-and-loop
COLOUR Black
NET WEIGHT, (SIZE 42) 1.32 kg

COMPLIANCE

CE Cat. II

EAC TP TC 019:2011

ASTM F2413-18
M/I/C/Mt/PR

ASTM F3445-21
SR

EN ISO 20345:2011
S3, SRC, HRO, M, CI, HI

FEATURES

- Anti-static properties
- Ergothan Shock Absorption System
- Heat-resistant upper
- Aluminium toecap
- Oil-resistant outsole
- ProNose toe reinforcement
- Nail protection in plasma-treated composite (PTC) textile
- Wide fit
- Heat-resistant outsole
- Water repellent

SIZE				ARTICLE NUMBER	EAN
EU	UK	US M	US W		
36	3	4	5	1948S-36	6408487545320
37	4	5	6	1948S-37	6408487545375
38	5	5.5	6.5	1948S-38	6408487545429
39	6	6.5	7.5	1948S-39	6408487545474
40	6.5	7.5	8.5	1948S-40	6408487545528
41	7	8	9	1948S-41	6408487545573
42	8	9	10	1948S-42	6408487545627
43	9	9.5	11	1948S-43	6408487545672
44	10	10.5	11.5	1948S-44	6408487545726
45	10.5	11	12.5	1948S-45	6408487545771
46	11	12	13	1948S-46	6408487545825
47	12	13	14	1948S-47	6408487545870
48	13	13.5	14.5	1948S-48	6408487545924

ejendals
Limavägen 28, SE-793 32 Leksand, Sweden
Phone +46 (0) 247 360 00 | info@ejendals.com | order@ejendals.com

All values for the specified product are indicated without tolerances and may vary to actual value for individual products. We reserve the right to modify or update the information in this document without prior notice.