
PRODUCT DATA SHEET proRange®

# 34-305

MaxiCut® Oil™ — Cut Level B ¾-Coated Knitwrist Glove






A Total glove length
B Wrist length
C Wrist width
D Palm width

**¾ coated knitwrist · NBR micro-foam**
Coating: Grey/Black · Liner: Green

## Product Overview

A lightweight glove designed for precision handling in oily environments where dexterity and protection are equally critical. Featuring a palm coating that repels oils and improves grip, it delivers EN 388 Cut Level B resistance for tasks involving light to moderate cut risks. The glove's streamlined design enhances fingertip sensitivity, while GRIPtech® and CUTtech® technologies work together to provide control and confidence when handling slick or sharp components. With a reinforced thumb crotch and skin-safe construction, it's built for comfort and durability across long shifts.

### Oil Resistance
LIQUItech® provides protection against oils, liquids and chemical splashes.

### Cut Level B Protection
CUTtech® fibres offer protection against minor cuts and abrasions. Ideal for lower-risk, high-precision environments.

### Secure Grip in Slippery Conditions
GRIPtech® micro-cup finish improves handling precision in wet, dry or oily environments, helping reduce accidents and fatigue.

### Skin-Safe & Ready to Wear
Pre-washed, OEKO-TEX® certified and dermatologically accredited. Part of ATG®'s HandCare® programme for skin health and user confidence.

TECHNOLOGIES INSIDE

LIQUItech® · DURAtech® · ERGOtech® · GRIPtech® Oil™ · HandCare® · CUTtech®

COLOURS Coating – Grey/Black · Liner – Green ENVIRONMENT Cut · Wet/Oily

## Product Information

| | |
|---|---|
| PRODUCT CODE | 34-305 |
| RANGE | MaxiCut® Oil™ (proRange®) |
| DESIGN | ¾ Coated Knitwrist |
| COATING | NBR (Nitrile Butadiene Rubber) |
| COATING TEXTURE | Micro-Foam with Non-Slip Grip |
| LINER | Glass, Nylon, Polyester, Spandex |
| COLOUR – COATING / LINER | Grey/Black / Green |
| PATENT NUMBER | EP 1 608 808 |
| PALM THICKNESS | 1.30 mm |
| LENGTH (SIZE 10) | 25 cm |
| SIZES | 6 (XS) – 11 (2XL) |
| WASHABLE | 40 °C / 104 °F (3 washing cycles) |
| OTHER VARIANTS | 44-505, 34-304, 34-450LP, 34-470LP, 34-504, 34-505, 44-304, 44-305, 44-504 |

## Standards & Certification

| STANDARD | NOTIFIED BODY | RESULT |
|---|---|---|
| EN ISO 21420:2020+A1:2024 | TÜV Rheinland | Pass |
| EN 388:2016+A1:2018 | TÜV Rheinland | **4331B** |

## Typical Performance Values

| | |
|---|---|
| EN 388 A. ABRASION RESISTANCE | > 8,000 cycles |
| EN 388 B. CUT RESISTANCE (COUP) | > 5.0 index |
| EN 388 C. TEAR RESISTANCE | > 50 N |
| EN 388 D. PUNCTURE RESISTANCE | > 20 N |
| EN 388 E. CUT RESISTANCE (ISO) | ≥ 5 N |

## Special Features

| | |
|---|---|
| SILICONE FREE | Yes |
| FDA 21 CFR 177.2600 COMPLIANT | Yes |

## Dimensions & Weight

| SIZE | 6 (XS) | 7 (S) | 8 (M) | 9 (L) | 10 (XL) | 11 (2XL) |
|---|---|---|---|---|---|---|
| **DIMENSIONS (mm)** | | | | | | |
| A TOTAL GLOVE LENGTH (±10 MM) | 210 | 220 | 230 | 240 | 250 | 260 |
| B WRIST LENGTH | 70 | 78 | 80 | 88 | 90 | 95 |
| C WRIST WIDTH | 72 | 83 | 85 | 85 | 87 | 88 |
| D PALM WIDTH (±3 MM) | 100 | 106 | 109 | 111 | 118 | 120 |
| OVERLOCK COLOUR | Blue | Red | Orange | White | Yellow | Black |
| **WEIGHT** | | | | | | |
| GLOVE WEIGHT / PAIR (±6 G) | 60 | 64 | 74 | 80 | 86 | 88 |
| GROSS WEIGHT (KG) | 5.5 | 5.8 | 6.5 | 7.0 | 7.4 | 7.5 |
| CARTON WEIGHT (KG) | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 | 1.0 |
| NET WEIGHT (KG) | 4.5 | 4.8 | 5.5 | 6.0 | 6.4 | 6.5 |

## Packaging

| | |
|---|---|
| PAIRS PER POLY BAG | 12 |
| POLY BAGS PER CARTON | 6 |
| PAIRS PER CARTON | 72 |
| CARTON DIMENSIONS | 500 × 295 × 200 mm |

## HandCare®

| | |
|---|---|
| SKIN HEALTH ALLIANCE DERMATOLOGICALLY ACCREDITED | Yes |
| REACH COMPLIANT | Yes |
| STANDARD 100 BY OEKO-TEX® (08.BH.57867) | Certified |
| WASHABLE | 40 °C / 104 °F |
| SANITIZED® | Yes |

ISO 14001 & ISO 9001 system certification (SGS / UKAS)
Datasheet issue date: 18/07/2019




AVAILABLE AT Armexia
armexia.com