PRODUCT DATA SHEET

SCBA 6.8 L Carbon Composite | 300 bar | 60 min

Self-Contained Breathing Apparatus (SCBA)

EN 137:2006 | EN 136:1998 | Alarm ≥ 90 dB | Visual Field up to 92%

MASTERS®



KEY SPECIFICATIONS

CYLINDER VOLUME **6.8 L**	CYLINDER PRESSURE **300 bar**
RATED SERVICE TIME **60 min**	CYLINDER SERVICE LIFE **15 years**
ALARM SOUND **≥ 90 dB**	MAX AIR FLOW **≥ 1000 L/min**

APPROVALS

EN 137:2006 Self-contained compressed-air BA	**EN 136:1998** Full-face mask

KEY DATA

DESCRIPTION	Self-Contained Breathing Apparatus (SCBA)
BRAND	MASTERS
STANDARD	EN 137:2006 | EN 136:1998
ORIGIN	China
CYLINDER	6.8 L Carbon Fiber Composite, 300 bar
PACKAGING	1 set per carton

TECHNICAL SPECIFICATIONS

MATERIALS	
CYLINDER	Composite carbon fiber
MASK	Kevlar head harness, silicone mask body, anti-fogging lens
BACKPACK	Aramid
MASK VISUAL FIELD	Up to 92%

PERFORMANCE	
RATED SERVICE TIME	60 min
CYLINDER SERVICE LIFE	15 years
INHALATION RESISTANCE	≤ 5 mbar (stated as ≤ 5 bar)
EXHALATION RESISTANCE	≤ 10 mbar (stated as ≤ 10 bar)
ALARM PRESSURE	55 ± 5 bar
ALARM SOUND	≥ 90 dB
MAX AIR FLOW	≥ 1000 L/min

AVAILABLE AT
Armexia
ARMEXIA
armexia.com