PRODUCT DATA SHEET

ULTRATRAIL BLACK LOW

S3 ESD HRO SRC – Black-Red

Art. No. 64.620.0 | Sizes 36–47 | Unisex | Metal-Free

albatros MADE TO PROTECT

ULTRATRAIL





Outsole



Heel

KEY DATA

PROTECTION	Fiberglass toe cap and flexible FAP® midsole
PLUS	Bumper of rubber in the toe area, special fit and last in women's sizes 36–40
UPPER	Leather with abrasion-resistant textile inserts
LINING	Breathable functional lining
FOOTBED	Anatomically formed comfit® AIR footbed
SOLE	XTS TRAIL – high-quality, 300 °C heat- and slip-resistant rubber outsole with IMPULSE.FOAM® midsole for optimal cushioning, stability and comfort
COLOUR	Black-Red
SIZES	36–47

FAP FLEXIBLE ANTI-PENETRATION

IMPULSE.FOAM®

XTS CROSS TERRAIN SOLE

Composite | Slip Resistant | HRO Sole | Unisex | Metal Free | ESD | DGUV 112-191

TECHNOLOGIES



Slip-Resistant XTS TRAIL Outsole

The easy-to-clean rubber outsole ensures perfect contact with the ground. It is non-slip, abrasion-proof and heat-resistant up to 300 °C (HRO). The specially designed cleat profile and the wide flex grooves guarantee optimal flexion, optimise the water-displacing properties (windshield wiper effect) and provide a secure hold on a wide variety of surfaces.



comfit® AIR Footbed

The newly developed, breathable ALBATROS® comfit® AIR footbed has elevations in the heel and ball area of the foot as well as a support of the longitudinal arch. This helps the foot keep its natural position in the shoe and stimulates the musculature while walking. The slip-resistant textile cover is odour-resistant, moisture-absorbing and washable at 30 °C.



IMPULSE.FOAM® Midsole

Ultimate comfort during long working days. The innovative IMPULSE.FOAM® midsole in two different densities reacts to each of your steps with an energy impulse. The IMPULSE.FOAM® not only returns the energy but also provides maximum cushioning and excellent stability.



Fiberglass Toe Cap

Fiberglass-reinforced composite toe cap with more space for the toes, lighter than a common steel cap, antimagnetic and thermally insulating.

Technical data as provided by the manufacturer.

Specifications subject to change without notice.

AVAILABLE AT Armexia

ARMEXIA

armexia.com