PRODUCT DATA SHEET CE Category II

TEGERA® Infinity 8812

Soft, Fully Dipped, Cut D Glove







Fully dipped · soft nitrile foam palm
15 gauge CRF® Technology liner · textile cuff

Product Overview

Dexterous cut-resistant glove, level D, suitable for assembly work. Great fit thanks to 15 gg knitting with CRF® cut-resistant technology. Fully dipped, with a super-soft nitrile foam-coated palm that provides good grip on greasy and oily surfaces. Reinforced thumb crotch for improved longevity. Protection against contact heat up to 100 °C / 212 °F. Skin friendly, with Derma-test and OEKO-TEX® certificates.

CHARACTERISTICS

High Level of Protection · Good Fingertip Sensitivity · Flexible · Durable · Good Grip · Comfortable

FUNCTIONS

Withstands Contact Heat up to 100 °C · Approved for Handling Foodstuffs · Reinforcement Between Index Finger and Thumb · Oil and Grease Resistant · Anatomically Designed

FEATURES

Cut Protection

CRF® Technology — Featured Brand
Engineered to protect. Tailored for comfort.

COLOUR Black COLLECTION TEGERA® Infinity Collection

Specifications

PRODUCT	TEGERA® Infinity 8812
TYPE	Cut resistant gloves, Heat protection gloves
CATEGORY	Cat. II
CUT RESISTANCE	Cut resistance level D
SIZE RANGE (EU)	6–11
LENGTH	225–275 mm
LINING MATERIAL	CRF® Technology, Glass fibre thread, HPPE, Nylon, Spandex
KNITTING GAUGE	15 GG
DIPPING MATERIAL	Nitrile, Nitrile foam, Water-based PU
GRIP DESIGN	Foam grip pattern
CUFF MATERIAL	Textile
COLOUR	Black
TYPE OF WORK	Medium weight
PAIRS PER BUNDLE / CARTON	6 / 120
DISPLAY TYPE	Bulk pack

Compliance

STANDARD	RATING
EN ISO 21420:2020	Listed
EN 388:2016+A1:2018	**4X43D**
EN 407:2020 (no flame protection)	**X1XXXX**
TP TC 019:2011	Listed
Markings shown	CE · UKCA · EAC
Food Contact	Approved for handling foodstuffs
OEKO-TEX® STANDARD 100	Certified (SE 14-214)
Dermatest Seal of Approval	Dermatest (2019)

EN 388:2016+A1:2018 — 4X43D

A Abrasion	B Cut (Coup)	C Tear	D Puncture	E Cut (ISO)
4	X	4	3	D

EN 407:2020 — X1XXXX

A Flame	B Contact Heat	C Convective	D Radiant	E Small Splash	F Large Splash
X	1	X	X	X	X

X = not tested or not applicable.

Prevents Risk Of

Cut injuries · Abrasion injuries · Blisters · Grazes · Scratches, lacerations · Contact with dirt · Drying out · Chapping · Contact with oil and fat

Primary Environments of Use

Cut risk environments · Moist environments · Oily and greasy environments · Dirty environments · Harsh environments

Primary Areas of Use

Fine assembly · Assembly · Machine operating · Building and construction · Carpentry · Installation work · HVAC installation · Sheet-metal work · Engineering · Transport work · Machine driving · Warehouse work · Airport work · Metalwork · Glass industry work · Repair work · Paper industry work · Service work · Shop work

Primary Industries of Use

Agriculture, forestry and fishing · Automotive manufacturing · Automotive repair and maintenance · Basic metals manufacturing · Building and construction · Electrical equipment manufacturing · Electricity and gas supply · Facility management services · Glass, ceramics and construction materials · Machinery and equipment manufacturing · Metal manufacturing and fabrication · Mining and quarrying · Public safety, security and defence · Pulp and paper · Retail and wholesale · Transport equipment manufacturing · Transportation and logistics · Warehousing

Sustainability

RECYCLED PACKAGING	50 %
LDPE (4)	50 %
TOTAL	50 %

Source: manufacturer's official product page (ejendals.com), Oct 2026.

AVAILABLE AT Armexia
armexia.com