PRODUCT DATA SHEET

PACAYA CLEAR

Clear-Lens Safety Glasses with Removable Foam Protection
Ref. PACA101CL0SFU0 (old ref. PACAYBLIN) – for Intensive Use

EN 166 1 FT / FT | EN 170 2C-1.2 | ANSI Z87.1-2003 Z87+ U6 | CE Cat. II | Anti-Fog / Anti-Scratch | UV400



PACAYA CLEAR – black nylon frame, clear lens, removable foam

KEY FEATURES

Removable Foam Protection
Absorbing foam gasket for increased comfort and optimal sealing

Anti-Fog / Anti-Scratch Lens
Polycarbonate, UV400; anti-scratch coating increases lifespan

Wide Field of Vision
Spherical visor, brow protection, side shields and vents

STANDARDS & CERTIFICATIONS

EN 166:2001	EN 170:2002	ANSI Z87.1-2003	CE – (EU) 2016/425	NOTIFIED BODY	EU TYPE-EXAM. CERT.
1 FT / FT	**2C-1.2**	**Z87+ U6**	**Cat. II**	**0530**	**AC 08027**
Lens / frame marking	UV filter	High impact · UV	PPE category	Certottica · Module B	Rev. 7

KEY DATA

REFERENCE	PACA101CL0SFU0 (old reference: PACAYBLIN)
BRAND	Delta Plus
DESCRIPTION	Clear-lens safety glasses with removable foam protection for intensive use
STANDARD	EN 166:2001 (1 FT / FT) · EN 170:2002 (2C-1.2) · ANSI Z87.1-2003 (Z87+ U6) · CE Cat. II
LENS	Polycarbonate, monoblock, curve 8 · Anti-fog / anti-scratch (classic) · UV400
FRAME	Black nylon · Temples with adjustable width and flexible tip · Absorbing foam gasket
COLOR	Clear lens / Black frame
WEIGHT	36 g
EAN13 / BOX CODE	3295249137465 / 13295249137462
PACKING	Multiple sales 100 · Minimum order quantity 10 · Carton weight 7.40 kg

TECHNICAL SPECIFICATIONS

FEATURES & BENEFITS

- **Comfort:** ample indirect venting on the top and bottom of the lens to reduce moisture infiltration and fogging.
- **Sealing:** removable absorbing foam for increased comfort and optimal sealing.
- **Fit:** wide frame brings a better fit for wider facial profiles.
- **Performance:** brow protection, side shields and vents; spherical visor for an extra-large field of vision.
- **Durability:** anti-scratch coating increasing lifespan.
- **Compatibility:** extra-flat temples for optimal comfort with ear muffs.

USE & APPLICATIONS

Risks: shock (impact), UV / IR
Use: inside
Sector: automotive
Optional accessory: cord
Variant: PACAYA CLEAR LYVIZ – ref. PACA101CL2SFU0 (old ref. PACAYLVIN)

TECHNICAL DETAILS – DELTA PLUS

TYPE / USE	Glasses · Inside
GLASSES STYLE	Monoblock, curved
LENS MATERIAL	Polycarbonate
LENS TREATMENT	Anti-fog, anti-scratch, UV400
LENS COLOR	Clear
LENS BASE CURVE	8
OPTICAL CLASS	1
LENS PROTECTION CLASS	1.2
MECH. STRENGTH (LENS)	F, T
MECH. STRENGTH (FRAME)	F, T
FRAME MATERIAL / COLOR	Nylon · Black
NOSE PAD MATERIAL	Polycarbonate
GASKET	Absorbing foam
TEMPLES	Adjustable width, flexible tip
BENEFIT	Color perception
WEIGHT	36 g

AVAILABLE AT
Armexia
armexia.com